

QUICK REFERENCE GUIDE



Rooftop Units - 60 HZ 3- to 12.5-ton packaged gas/electric and electric/electric rooftop units

3- to 6- Ton Packaged Rooftop Performance Data (Gas or Electric Heat) - Standard Efficiency

Size - (Tons)	3	3	4	4	5	5	6	6
Efficiency	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Model Number	ZCA/ZGA 036S4B	ZCB/ZGB 036S4B/E	ZCA/ZGA 048S4B	ZCB/ZGB 048S4B/E	ZCA/ZGA 060S4B	ZCB/ZGB 060S4B/E	ZCA/ZGA 072S4B	ZCB/ZGB 074S4T
Blower Type	Single Speed Belt Drive	Single Speed Belt Drive/ ECM Direct Drive	Single Speed Belt Drive	Single Speed Belt Drive/ ECM Direct Drive	Single Speed Belt Drive	Single Speed Belt Drive/ ECM Direct Drive	Single Speed Belt Drive	Two Speed Belt Drive
Net Cooling Capacity (Btuh)	34,600	35,000	45,000	45,500	57,000	57,000	68,000	67,000
Cooling Stages	1	1	1	1	1	1	1	1
Nominal Supply Air (cfm)	1200	1190	1550	1380	1650	1725	2025	2200
SEER	13.0	14.0	13.0	14.0	13.0	14.0	----	----
IEER	----	----	----	----	----	----	12.0	15.0
EER	11.5	11.7	10.6	11.0	10.7	11.0	11.2	11.2
Gas Heat Size (kBtu)	65, 108	65, 108	65, 108, 113 & 150	65, 108	65, 108, 113 & 150	108, 150	65, 108, 113 & 150	65, 81,108,113 & 150
Electric Heat Size (kW)	5, 7.5, 10 & 15	5, 7.5, 10 & 15	5, 7.5, 10, 15 & 22.5	5, 7.5, 10, 15 & 22.5	5, 7.5, 10, 15 & 22.5	5, 7.5, 10, 15 & 22.5	7.5, 10, 15, 22.5 & 30	7.5, 10, 15, 22.5 & 30
Blower Motor Size (HP)	1 & 1.5	1 & 1.5 0.5 (ECM)	1 & 1.5	1 & 1.5 0.75 (ECM)	1 & 1.5	1 & 1.5 1.0 (ECM)	1, 1.5 & 2	2
Net. Weight (lbs) G/E	484	524	498	533	530	592	640	640
Net. Weight (lbs) E/E	451	474	465	483	497	568	568	568
Cabinet Size - H x W x L (in)	37 x 48 x 76	37 x 48 x 76	37 x 48 x 76	37 x 48 x 76	37 x 48 x 76	45 x 48 x 76	45 x 48 x 76	45 x 48 x 76
Filter (Quantity / Size)(in)	(4) 14 x 20 x 2	(4) 14 x 20 x 2	(4) 14 x 20 x 2	(4) 14 x 20 x 2	(4) 14 x 20 x 2	(2) 16 x 20 x 2 (2) 20 x 20 x 2	(2) 16 x 20 x 2 (2) 20 x 20 x 2	(2) 16 x 20 x 2 (2) 20 x 20 x 2
Sound (dBA)	78	78	80	80	83	78	84	84

QUICK REFERENCE GUIDE



Rooftop Units - 60 HZ 3- to 12.5-ton packaged gas/electric and electric/electric rooftop units

7.5- to 12.5- Ton Packaged Rooftop Performance Data (Gas or Electric Heat) - Standard Efficiency								
Size - (Tons)	7.5	7.5	8.5	8.5	10	10	12.5	12.5
Efficiency	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Model Number	ZCB/ZGB 092S4B	ZCA/ZGA 092S4M	ZCB/ZGB 102S4B	ZCA/ZGA 102S4M	ZCB/ZGB 120S4B	ZCA/ZGA 120S4M	ZCB/ZGB 150S4B	ZCA/ZGA 150S4M
Blower Type	CAV	MSAV	CAV	MSAV	CAV	MSAV	CAV	MSAV
Net Cooling Capacity (Btuh)	88,000	86,000	97,000	97,000	115,000	115,000	136,000	136,000
Cooling Stages	2	2	2	2	2	2	2	2
Nominal Supply Air (cfm)	2750	2800	3250	3250	3100	3800	3800 (ZG) 3700 (ZC)	4400
SEER	----	----	----	----	---	---	---	---
IEER	12.7 (ZG) 12.9 (ZC)	13.0 (ZG) 13.2 (ZC)	12.7 (ZG) 12.9 (ZC)	13.0 (ZG) 13.2 (ZC)	12.7 (ZG) 12.9 (ZC)	13.0 (ZG) 13.2 (ZC)	12.2 (ZG) 12.4 (ZC)	12.0 (ZG) 12.2 (ZC)
EER	11.0 (ZG) 11.2 (ZC)	11.0 (ZG) 11.2 (ZC)	11.0 (ZG) 11.2 (ZC)	11.0 (ZG) 11.2 (ZC)	11.0 (ZG) 11.2 (ZC)	11.0 (ZG) 11.2 (ZC)	10.8 (ZG) 11.0 (ZC)	10.8 (ZG) 11.0 (ZC)
Gas Heat Size (kBtuh)	130, 180 & 240							
Electric Heat Size (kW)	7.5, 15, 22.5, 30 & 45				15, 22.5, 30, 45 & 60			
Blower Motor Size (HP)	2, 3 & 5							
Net. Weight (lbs) G/E	902	902	922	922	1154	962	1052	1052
Net. Weight (lbs) E/E	854	854	874	874	1106	914	1004	1004
Cabinet Size - H x W x L (in)	49 x 61 x 96							
Filter (Quantity / Size)(in)	(4) 20 x 24 x 2							
Sound (dBA)	84	84	84	84	84	84	91	91

